# Machine Tester Delta Pro7 La Delta Delta





- Large Liquid Crystal Display with backlight
- IR, timed IR, DAR, PI
- Resistance measurement: 200 G $\Omega$  1 kV
- High current 2 mA short circuit current
- Rechargeable NIMH battery + AC Adaptor
- CAT IV 600 V safety rating up to 3000 m
- Dedicated voltmeter function 1000V AC or DC
- Both Analog & Digital Display

#### **High Performance Specification**

Tests all types of AC/DC motors (any voltage) including induction, synchronous, and single & three phase motors. The electrical health of all motor components is evaluated, including stator windings and rotor; associated connections and cables.

Managers and engineers who are responsible for the reliability of motors will appreciate the enhancements we added to the Delta Pro 7 because it empowers their technicians to efficiently and accurately evaluate motors whether they are in the field or on the shop floor.

This helps improve motor reliability, increase technician and asset productivity, and reduce energy consumption.

High performance features include bargraph, built-in memory, leak current and voltage testing, and DAR and PI calculation capabilities to help shorten work time associated with field insulation testing.



#### **Predict Faults** Before They Happen

Detects faults at their earliest stages before motor failure, including deteriorating or contaminated insulation, as well as "deep" winding faults.



#### Than 3 Minutes

Analyze complete stator and rotor electrical health in AC induction & synchronous motors.

Get the motor health data you need to make a quick and informed decision.

## Insulation & Rotating Achine Tester Delta Pro7



#### **Technical Specifications**

Function	Range / Values		
Test modes	Insulation resistance (PI, DAR), Voltmeter, continuity (resistance) tests, 4 - Wire low resistance test, motor direction, inductance, capacitance and resistance Meter (LCR), temperature		
Insulation Resistance			
Resistance	Resistance range 100 $\Omega$ up to 200 G $\Omega$ (Resolution 0.1k $\Omega$ )		
Accuracy	± 2% ± 2Digit		
Test Voltage	Test Voltage: upto 1 kV in10 V steps		
Accuracy	± 2% ± 2Digit		
Short Circuit/ Capacitor Charge Current	2 miiliAmp		
Guard terminal performance	Resistance range 100 $\Omega$ up to 200 G $\Omega$ (Resolution 0.1k $\Omega$ )		
Voltmeter			
AC/ DC Voltage Measurement	DC: 0 - 1000 V AC: 10 mV - 1000 V		
Accuracy	± 3%		
Continuity			
Measurement	0.01 Ω to 1 MΩ		
Accuracy	±5% ±2 digits		
Current limit	Selectable between 20 mA and 200 mA		
Capacitance			
Range	0.1 nF - 1 mF		
Accuracy	±6.0% ±2 digits		
4- Wire Low Resistance Test			
Test current	200 mA dc		
Range	1 mΩ to 20 Ω		
Resolution	0.01 mΩ		
Accuracy	± 0.25% rdg. ± 10 digits, accuracy stated includes forward and reverse Measurements.		
Direction Of Motor	L1-L2-L3 or L3-L2-L1		
Inductance	2mH to 1H		
Diode test	0.01 V to 3.00 V		

### 



Temperature Measurement		
Range	-20 °C to 200 °C	
Instrument resolution	0.1 °C	
Instrument accuracy	± 2.0 °C	
Protection	500 mA, 1000V ceramic fuse, high break capacity HBC, 30 kA minimum	
Interface	USB	
Data Logging/Memory	Yes, 300 Results can be stored with Date/ Time stamp	
Operating temperature	- 10 °C to 50 °C	
Storage temperature	- 20 °C to 60 °C	
Humidity	90% RH	
IP rating	IP54	
Safety	Meets the requirements of IEC 61010-1, CATIV 600 V	
Guard terminal performance	<10 % error at 500 $k\Omega$ parallel circuit resistance with 100 $M\Omega$ load.	
EMC	As per IEC61326-1	
Enclosure Material	Polycarbonate	
Keyboard	Alphanumeric, sealed tactile switches with backlight overlay	
Weight	1 kg	
Dimensions	126 x 218 x 51 mm	
Battery	Rechargeable NIHM battery	
Power	90 - 264 V rms AC Voltage	

#### **Ordering Information**

Code	Description
DELTA Pro7	Insulation & Rotating Machine Tester Included accessories Test Cables with Alligator Clips, Quick Reference Card USB-IR Cable Installation Guide IP67 Hard Case, Temperature Probe, Kelvin Test Probe Set, Certificate of Calibration, Heavy Duty Alligator Clip Leads.

### msuiation & Rotating ▲ Delta ™ Machine Tester Delta Pro7



#### Ordering Information - Optional Accessories

Code	Description
TL270HC3	3 mtrs. Test Lead Set with Insulated Alligator clip
TL270HC10	10 mtrs. Test Lead Set with Insulated Alligator clip
TL270HC15	15 mtrs. Test Lead Set with Insulated Alligator clip
AL270HC	Alligator Clip High Current
ATA75C	Alligator To Alligator Test Lead Set
ВТА75	Banana To Alligator Test Lead Set
ATS75	Alligator Clip to Spade Lug
*Note	Other Accessories on Request